



Since 1994, DIGITAL LEADER Axis Sensitive Co. Ltd



Industrial Explosion Proof Load Cell

MODEL : Ex80



Zone 2등급



제품 규격 [UNIT : mm]

Product Specification





운영체제	Windows® 10 Pro
Moblie Computing Platform	<ul style="list-style-type: none"> Intel Atom® x5-Z8350 Processor 1.44GHz, burst up to 1.92GHz - 2MB Cache
VGA 컨트롤러	<ul style="list-style-type: none"> Intel® HD Graphics
디스플레이	<ul style="list-style-type: none"> 8" IPS TFT LCD WXGA (1280 X 800) 600 nits LumiBond™ display with Getac sunlight readable technology Capacitive touchscreen with glove on
저장장치 및 메모리	<ul style="list-style-type: none"> 4GB LPDDR3 128GB eMMC
키보드	<ul style="list-style-type: none"> 6 tablet buttons(Windows, Power, Programmable Button x 2, Volume Up, Volume Down)
포인팅 디바이스	<ul style="list-style-type: none"> Touchscreen - Capacitive multi-touch screen
I/O 인터페이스	<ul style="list-style-type: none"> FHD Webcam x 1 8M Pixels auto focus rear camera with LED flash x 1 Docking connector Optional SIM card slot x 1

통신 인터페이스	<ul style="list-style-type: none"> ▪ Wi-Fi 802.11 a/b/g/n ▪ Bluetooth (v4.0)i ▪ Dedicated GPS (with internal antenna) ▪ Optional 4G LTE mobile broadband
소프트웨어	<ul style="list-style-type: none"> ▪ Getac Utility (Including Power Mnanager) ▪ Optional Absolute DDS® Persistence
보안기능	<ul style="list-style-type: none"> ▪ TPM 2.0 ▪ HF RFID reader
전원	<ul style="list-style-type: none"> ▪ Office Dock (Charging cradle with AC adapter, 24W, 100-240VAC, 50 / 60Hz)ii ▪ Li-Ion battery (7.4V, 4200mAh)
크기 및 무게	<ul style="list-style-type: none"> ▪ 240 x 155 x 29mm (9.4” x 6.1” x 1.14”) ▪ 1.48kg (3.28 lbs)iii
내구성 및 견고성	<ul style="list-style-type: none"> ▪ MIL-STD-810G certified and IP67 certified ▪ Vibration & drop resistant ▪ 6 feet drop resistant ▪ Salt fog certified
사용환경	<ul style="list-style-type: none"> ▪ Temperature <ul style="list-style-type: none"> - Operating : -21°C to 50°C / -5.8°F to 122°F - Storage : -51°C to 71°C / -60°F to 160°F ▪ Humidity <ul style="list-style-type: none"> - 95% RH, non-condensing
Explosion Protection	<ul style="list-style-type: none"> ▪ ATEX / IECEx <ul style="list-style-type: none"> - Ex II 1 GD - Ex ia op is IIC T4 Ga - Ex ia op is IIC T135°C Da

Explosion Protection

- UL913
 - Class I, Zone 0, AEx ia op is IIC T4 Ga
 - Class II, Zone 20, AEx ia op is IIIC T135°C Da
 - Class I, Division 1, Groups A, B, C, D
 - Class II, Division 1, Groups E, F, G
 - Class III, Division 1

[제품의 모든 스펙은 사전에 예고 없이 변경 될 수 있습니다.]



- 4G LTE mobile broadband
- 1D/2D Imager Barcode Reader (옵션)

- ▶ ATEX & IECEx 인증완료
- ▶ 8” HD LumiBond® Sunlight Readable display, advanced touch modes, front & rear cameras, HF RFID reader, dedicated GPS
- ▶ Thin and compact with optional hand or shoulder strap and office dock for maximum mobility.
- ▶ Extremely rugged, MIL-STD-810G and IP67 certified, salt fog resistant